

● Parameter

SMQT®

Boltahe ng Operating	DC12V
Naitala na kapangyarihan na output	15W
Kagamitan sa Pabahay	Mga materyales sa retardant ng apoy
Madalas na tugon	800HZ ~ 15KHZ
SNR	≥82db
Malakas ang output	150db
Temperatura ng pagtatrabaho	-10 °C ~ 65 °C
Katamtaman	40% hanggang 95%

● Introduction

SMQT®

Ginagamit ng NV020S ang pangunahing pagproseso ng boses ng boses ng boses, na may pang-industriya na pagganap at katatagan ng reticle;

Mataas na lakas ng apoy retardant ABS materyal, pagproseso ng spray ng ibabaw, matibay, mahabang buhay ng serbisyo;

Ang built-in dual output Philips audio amplifier, malakas, mataas na kahulugan;

Nag-iisang power supply, epektibong paggamit ng paggamit ng kuryente;

Saklaw: langis, mataas na presyon, mina, nakakalason, ibon sa paliparan at iba pa.

Ang electronic sirena ay ang alarm small sirena 115db na ginamit gamit ang alarm alarm at antif alarm.

● Dimesion Picture

SMQT®





1

Fire-proofing materials

Fire-proofing materials

High-strength fire retardant ABS material, the surface spray processing, durable, long service life.



2

Alarm sounds great

Alarm sounds great

NVozoS do use voice chip voice processing core, with industrial-grade performance and stability of the reticle;

Built-in dual output Philips audio amplifiers, loud, high definition.



3

Rotating stents

Rotating stents

Single power supply,
effective utilization of
power usage.

It can set on the
floor or wall, 90°
Rotating stents.



4

Wide applicability

Wide applicability

High-strength fire retardant ABS
material, the surface spray
processing, Scope: oil, high
pressure, mines, toxic, airport
bird and so on.

● Packing list

SMOT

Qty	50 / kahon
Mga pagtutukoy ng Packing	57 * 57 * 23.5 (cm)
Ang bigat ng packing	16.46Kg



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

