Wired embedded magnetic contact

NC/NO mode optional

35±5(mm) gap distance

Max voltage≤100VDC, Max current≤500mA

Suitable for metal door or window

White/Brown color optional

24g weight

SMQT

Parameter

SMQT

parametro	
Pangalan ng Produkto	Emedded magnetic contact sensor
modelo	EB-136
sukat	Φ19 × 25 (mm)
code mode	NO / NC (opsyonal)
puwang	35 ± 5 (mm)
Max boltahe	≤100V DC
Max kasalukuyang	≤500mA
Max rating	≤10W
kulay	Brown / White (opsyonal)
suit para sa	Metal pinto o window
materyal	Fireproof ABS pabahay
Paggawa temperatura	-10 ℃ ~ 50 ℃
net timbang	24g

In-kind shooting

SMQT

•*Feature*

EB-136

Dimension:	Φ19*25(mm)
Material:	ABS
Max Gap:	≤40mm
Install way:	Drill hole install
Wire:	22# wire 40cm
Power:	0.5A 10W

Fire-proofing materials

Adopt ABS flame retardant material, fire retardant safer,connecting with 22 # wire, total length of 30 cm. Suitable for metal doors and cabinet door, etc.

Waterproof seal

Using imported PC glue sealing, close the magnet and wiring, waterproof, and durable leakage, using more safe and more comfortable

Strong magnetism

Magnetic strength, which can be installed directly drilling, stable performance.

•Packaging & shipping

SMQT

listahan packaging	
Pangalan ng Produkto	Emedded magnetic contact sensor EB-136
Dami	600 PC ng bawat karton
carton laki	38 * 30 * 30 (cm)
timbang	16kg

•Office show

SMQT

•*Exhibition*

SMQT