

Touch door release button

LED light indication

Touch iduction

Plexiglass panel

2 sizes optional

500000 times mechanical test.

SMQT®



• Parameter

SMQT®

parametro	
Pangalan ng Produkto	LED back light door button switch
modelo	EA-20
sukat	Model A: 86 × 56 × 25 (mm) Model B: 86 × 86 × 25
input boltahe	DC 12V
Standard istraktura	hawakan pleksiglas
Mechanical test	500,000 beses test
Angkop na hanay	Hollow Door
kulay	Black panel, Sliver frame
paggamit	Access control sysetm at doorphone sistema
Kamag-anak Humidity	0 ~ 95%
Environment temprature	-20 °C -50 °C
net timbang	Model A: 0.06kg Model B: 0.09kg

• Introduction

SMQT®





EA-20A



EA-20B

1 Superior Design

Touch push button design simple and beautiful, Panel using organic glass materials, touch induction to open the door, button USES the interactive design of light touch response. Internal using PC rubber production, high temperature resistant do not fade

Resistance to heat shock Organic glass touch responsive



2 Product components

500,000 times test qualified, the relay switch power output, (NO NC COM) 3 lines button suitable for all Access control system

NO NC COM, 3 lines



3 Strong stability

Waterproof and dustproof more durable and strong, resistance to high temperature shock do not fade.

Waterproof and Dustproof Stable solid long life

• Application

SMQT



Switch Power Supply



Touch Induction
Door Release button EA-20

Single Door Access
control Keypad

• Packaging & shipping

SMQT

listahan packaging	
Pangalan ng Produkto	EA-20 LED back light door button switch
Dami	100 PC ng bawat karton
carton laki	37 * 30 * 29 (cm)
timbang	12kg



• Office show

SMQT



• Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....