

Specification	
Model	EA-25
Dimension	88×88×20(mm)
Standard Structure	Stainless steel panel With Key
Rating current	3A 36V DC Max
Contact Output	NC/COM
Mechanical test	100.000 times test
Optional Accessories	Concealing Box
Suitable range	Hollow Door
Color	grey
Safe Type	Waterproof, Defense to duplicate the key
Usage	Access control sysetm and doorphone system
Relative Humidity	0~95%
Environment temprature	-20 °C-55 °C
Panel Material	Stainless steel panel, wire drawing finished
Net weight	0.16kg

what features of our emergency button with the key?





Stainless Emergency
Door Release Button
EA-25

LED light indicator Waterproof apperance and Durable Anti-duplicated keys

Stainless steel panel, wire drawing oil processing.



# **IN-KIND SHOOTING**



### **APPLICATION**



# **SIMILAR PRODUCT**



### **OFFICE SHOW**













### **CUSTOMER**













### **EXHIBITION**



#### **CERTIFICATION**



#### **HOW TO COOPERATE**



# PACKAGING & SHIPPING

Detection+Packing+Sealing+Fnishing+International Express



















A:Yes, we are willing to offer trial sample order to you for quality test. Mixed samples are acc eptable.

#### Q: What is the lead time?

A:Sample needs 1-3 working days, mass production time needs 10-15 working days for order less than 5000pcs.

#### Q: Do you have any MOQ limit?

A:EXW MOQ is 100pcs under blank box.

#### Q:How do you ship the goods and how long does it take arrive?

A:The sample will be sent to you by optional shipping service (couriers, air, and sea). The delivery time depends on the shipping service.

#### Q: How will we proceed the order if I have logo to print?

A Firstly, we will prepare artwork for visual confirmation. If the color and position are right, we would make sampling firstly from silk print factory and take picture for your second confirmation before mass production.