

# What specifications of our EB-117A?

12v/24v DC photoelectric smoke detetor with 20sqm detecting range	
Sound and Light alarm	
Operating voltage:	12VDC
Static current	≤2mA
Alarm current	≤15mA
Enviroment temperature	-10°C~+50°C
Dimension:	Ø104×51(mm)
Alarm output	NO/NC
Humidity	≤90%
Alarm mode	LED indication network output
Detection range	20sqm
Reset mode	Auto/power off reset
Weight	222g

# What features of our EB-117 photoelectric smoke detector?



- 1.Wired photoelectric smoke detector
- 2.CE&ROHS certificate
- 3.4 wires terminal
- 4. Suitable for fire alarm and alarm system
- 5.2 years warranty, welcome OEM

### **IN-KIND SHOOTING**



# **SIMILAR PRODUCT**































# **CUSTOMER**











# **EXHIBITION**



#### **CERTIFICATION**



## **PACKING & SHIPPING & PAYMENT**



# **FAQ**

### Q:Can I have a sample order?

A:Yes, we are willing to offer trial sample order to you for quality test. Mixed samples are acc eptable.

### Q: What is the lead time?

A:Sample needs 1-3 working days, mass production time needs 10-15 working days for order less than 5000pcs.

#### Q: Do you have any MOQ limit?

A:EXW MOQ is 100pcs under blank box.

#### Q: How do you ship the goods and how long does it take arrive?

A:The sample will be sent to you by optional shipping service (couriers, air, and sea). The delivery time depends on the shipping service.

#### Q:How will we proceed the order if I have logo to print?

A:Firstly, we will prepare artwork for visual confirmation. If the color and position are right, we would make sampling firstly from silk print factory and take picture for your second confirmation before mass production.