



## • *Parameter*

**SMQT**

<b>Specification</b>	
Product name	2 beams outdoor infrared perimeter detector
Model	ABT-20 ABT-40 ABT-60 ABT-80 ABT-100
Distance	20m 40m 60m 80m 100m (outdoor) 60m 120m 180m 240m 300m(indoor)
Operating voltage	13.8-24vDC 11-18vAC
Operating current	40-65mA
Induction speed	50-700m/sc
Environment temp	-20°C-50°C
Alarm output	NO/NC
Anti-demolition output	NC
Level adjustment	180°(±90°)
Vertical adjustment	±10°
Material	PC resin

## • *Introduction*

**SMQT**



• *Feature*

**SMQT**



Sealed integration structure is able to work in the harsh environment

Automatically regulate to confront with fog or inclement weather

Sensitivity (AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built-in integrated optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes, low-power digital

---

## • *Installation*

**SMQT**



## ● *Packaging & shipping*

**SMQT**

<b>Packaging list</b>	
Product name	ABT 2 beams outdoor infrared perimeter detector
Qty	20 pcs per carton
Carton size	51*48*38(cm)
Weight	21kg



## • Office show

SMQT®



## • Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair