



Product Name:	3A 36V DC plastic door release button for hollow door
Dimensions:	86*86*20mm
Standard Structure:	Fireproof Material
Current Rating:	3A@36VDC Max
Output Contact:	NC\NO\COM
Mechanical Life:	100000 tested
Suitable for Door:	Hollow Door
Operating temp:	-10~+55°C(14-131F)
Panel Material:	Fireproof Material
Weight:	0.15kg

what features of our EA-26A/B/C?



1. Plastic door release button for access control system

2. 100,000 times mechanical test

3. Fireproof ABS material panel

4. 3 models appearance optional

5. 2 years warranty, welcome OEM

IN-KIND SHOOTING



APPLICATION



Switch power supply



Converter
(RS232 to RS485)



Door release
button EA-26



Standalone
controller



PC



OFFICE SHOW



CUSTOMER



EXHIBITION



CERTIFICATION



HOW TO COOPERATE



PACKAGING & SHIPPING

Detection+Packing+Sealing+Finishing+International Express



Inquiry



Contract



Testing and packing



Receiving



Reply

Receive payment&Product

Delivery



FAQ

Q: Can I have a sample order?

A:Yes, we are willing to offer trial sample order to you for quality test. Mixed samples are acceptable.

Q: What is the lead time?

A:Sample needs 1-3 working days, mass production time needs 10-15 working days for order less than 5000pcs.

Q: Do you have any MOQ limit?

A:EXW MOQ is 100pcs under blank box.

Q:How do you ship the goods and how long does it take arrive?

A:The sample will be sent to you by optional shipping service (couriers, air, and sea). The delivery time depends on the shipping service.

Q: How will we proceed the order if I have logo to print?

A:Firstly, we will prepare artwork for visual confirmation. If the color and position are right, we would make sampling firstly from silk print factory and take picture for your second confirmation before mass production.