

Wired embedded magnetic contact

NC/NO mode optional

35±5(mm) gap distance

Max voltage≤100VDC, Max current≤500mA

Suitable for metal door or window

White/Brown color optional

24g weight

SMQT®



Name:	Cheap recessed magnetic door lock for wooden door/window EB-136
Dimension:	Φ19*25mm
Operating Voltage:	12V DC (one 23A battery)
Battery Life:	2-3year
MAX Current:	≤500mA
MAX Voltage:	≤100VDC
MAX Rating:	≤10W
Code Mode:	NO/NC
Material:	fireproof ABS housing
Gap:	20±5mm
Suit for:	wooden door or window
Weight:	8g

What Features of our magnetic contact EB-136?



1. Round magnetic contact for window /wooden.
2. fireproof ABS housing material
3. Gap: $20\pm 5\text{mm}$ Color : White /Brown ;Contact mode: NO/NC

IN-KIND SHOOTING



APPLICATION



SHOW CASE



OFFICE SHOW



CUSTOMER



EXHIBITION



Trade terms:	EXW
Payment terms:	T/T, Western union, Paypal etc
Delivery time:	Normal order within 7 days, bulk order 10-15days
Packing:	Neutral paper box and paper carton
Shipping:	Express company or by sea, by air or appointed by buyer

FAQ

Q:Can I have a sample order?

A:Yes, we are willing to offer trial sample order to you for quality test. Mixed samples are acceptable.

Q: What is the lead time?

A:Sample needs 1-3 working days, mass production time needs 10-15 working days for order less than 5000pcs.

Q: Do you have any MOQ limit?

A: EXW MOQ is 100pcs under blank box.

Q: How do you ship the goods and how long does it take arrive?

A: The sample will be sent to you by optional shipping service (couriers, air, and sea). The delivery time depends on the shipping service.

Q: How will we proceed the order if I have logo to print?

A: Firstly, we will prepare artwork for visual confirmation. If the color and position are right, we would make sampling firstly from silk print factory and take picture for your second confirmation before mass production.

Q: Does alarm panel work with any sensor?

A: The alarm panel can work with all dry contact wired detectors and wireless detector, including almost all of the wireless sensors from Chinese manufacturers. The wireless encode and decode is EV1527 or our wireless sensors.