

● Parameter

SMQT

Product Size	86L * 86W * 39H (mm)
Input voltage	DC12V
Contact output	NO / NC / COM
Durability test	500,000 times aging tested
For Type	For a variety of narrow door frames
Temperature	-20 °C ~ + 50 °C
Applicable humidity	0 to 95% (relative humidity)
Sensing distance	10cm
Qty	100

● Introduction

SMQT

- Infrared optical technology
- IP-55 grade protection level / SUS 304 stainless steel plate
- Against spread of infectious diseases (protection of health)
- Relay switch output

Dual LED indicator sensor standby or close

1) Sensor Standby: blue light-emitting diodes, blue lights

2) provide access to the sensor in 10 cm, red light

· Industrial Protection level (waterproof, dustproof): IP-55

· Contact Rating: 3A / 120V AC, 30V DC

· Operating voltage: DC 12V

Operating temperature range: 20-55 °C

· Lifetime: 100000 times

Weight: 85 g

The access control door release button is the stainless steel push exit button.

● Dimesion Picture

SMQT



● Installations

SMOT®



● Features

SMOT®

1 Durable and Reliable
more than 5 years life time

2 Well-made
drawing panel, touch feeling is extraordinary

4 Installation
easy install



3 Welcome OEM
print logo

5 Technology-leading
Anti-interference, induction distance is adjustable



Qty	100 / box
Packing Specifications	46.5L * 37.5W * 28H (cm)
Packing weight	10.6Kg

● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....