

Specification	
Product name	Wired Magnetic Door Contact Sensor
Model number	EB-136
Dimensions	Φ19 * 25 (mm)
Connection	Normally open / normally closed
Operating distance	35 ± 5 (mm)
Maximum pressure	≤100VDC
Load current	≤500mA
Working Power	≤10W
Housing Material	ABS fireproof material
Shape color	Brown / White
Scope	Iron door or window
product weight	24g

**Feature:** Beautiful appearance, high vibration resistance

**Material:**importABSshell;

Japan OKI reed switch;

1007# / 22 # 350mmUL wire

Color: white, brown

Working distance: 30-40mm

Switch Type: NC --- normally closed (open circuit alarm)

NO ---Normally open (path alarm)

NO& NC --- normally open normally closed

**Fixed form:** Embedded



Dimension:  $\Phi$  16\*21

Material: ABS

Max Gap: 20mm

Install way: Drill hole install


Wire : 22# wire 40cm

Power : 0.5A 10W

**2 Color optional**



**White**



**Brown**



● Features

**SMOT**

## Fire-proofing materials

Adopt ABS flame retardant material, fire retardant safer, connecting with 22 # wire, total length of 30 cm. Suitable for metal doors and cabinet door, etc.



## Waterproof seal

Using imported PC glue sealing, close the magnet and wiring, waterproof, and durable leakage, using more safe and more comfortable



## Strong magnetism

Magnetic strength, which can be installed directly drilling, stable performance.

### ● Packing list

**SMQT**

Specification	
Qty	500 / box
Packing Specifications	37.5L * 29.5W * 20H (cm)
Packing weight	12.8Kg





● Exhibitions



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....