

Specification	
Product name	Wired Magnetic Door Contact Sensor
Model number	EB-136
Dimensions	Φ19 * 25 (mm)
Connection	Normally open / normally closed
Operating distance	35 ± 5 (mm)
Maximum pressure	≤100VDC
Load current	≤500mA
Working Power	≤10W
Housing Material	ABS fireproof material
Shape color	Brown / White
Scope	Iron door or window
product weight	24g

Feature: Beautiful appearance, high vibration resistance

Material: import ABS shell;

Japan OKI reed switch;

1007# / 22 # 350mmUL wire

Color: white, brown

Working distance: 30-40mm

Switch Type: NC --- normally closed (open circuit alarm)

NO --- Normally open (path alarm)

NO& NC --- normally open normally closed

Fixed form: Embedded



Dimension: $\Phi 16*21$

Material: ABS

Max Gap: 20mm

Install way: Drill hole install


Wire : 22# wire 40cm

Power : 0.5A 10W

2 Color optional



White



Brown



● Features

SMOT

Fire-proofing materials

Adopt ABS flame retardant material, fire retardant safer,connecting with 22 # wire, total length of 30 cm. Suitable for metal doors and cabinet door, etc.



Waterproof seal

Using imported PC glue sealing, close the magnet and wiring, waterproof. and durable leakage, using more safe and more comfortable



Strong magnetism

Magnetic strength, which can be installed directly drilling, stable performance.

Packing list

SMQT

Specification	
Qty	500 / box
Packing Specifications	37.5L * 29.5W * 20H (cm)
Packing weight	12.8Kg





● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair