

● Parameter

SMQT®

Operating Voltage	DC12V
Rated output power	15W
Housing Material	ABS fire retardant materials
Frequency response	800HZ ~ 15KHZ
SNR	≥82db
Output loudness	150db
Working temperature	-10 °C ~ 65 °C
Humidity	40% to 95%

● Introduction

SMQT®

NV020S do use voice chip voice processing core, with industrial-grade performance and stability of the reticle;

High-strength fire retardant ABS material, the surface spray processing, durable, long service life;

Built-in dual output Philips audio amplifiers, loud, high definition;

Single power supply, effective utilization of power usage;

Scope: oil, high pressure, mines, toxic, airport bird and so on.

The electronic siren is the alarm small siren 115db used with the fire alarm and antif alarm.

● Dimesion Picture

SMQT®





1

Fire-proofing materials

Fire-proofing materials

High-strength fire retardant ABS material, the surface spray processing, durable, long service life.



2

Alarm sounds great

Alarm sounds great

NVozoS do use voice chip voice processing core, with industrial-grade performance and stability of the reticle;

Built-in dual output Philips audio amplifiers, loud, high definition.



3

Rotating stents

Rotating stents

Single power supply, effective utilization of power usage.

It can set on the floor or wall, 90° Rotating stents.



4

Wide applicability

Wide applicability

High-strength fire retardant ABS material, the surface spray processing, Scope: oil, high pressure, mines, toxic, airport bird and so on.

● Packing list

SMOT

Qty	50 / box
Packing Specifications	57 * 57 * 23.5 (cm)
Packing weight	16.46Kg



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

