

## ● Parameter

SMQT

Specification	
Product name	Wired Alarming Strobe light
Model	EB-169
Rated voltage	DC12V DC24V
Flashing frequency	90 beats / min
Operating Voltage	9-15VDC 20-28VDC
Light way	LED lights glow
Working current	12V≤80mA / 24V≤100mA
Power lights	2W 5W
Life	≥1000 hours (standard power continuous operation)
size	72 * 42 (mm)

## ● Introduction

SMQT



### *Combination of fixed base plate*

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

### *Strobe indicator light*

LED lights, flash frequency up to 90 times a minute.







## *Strobe Alarming light*

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

## *LED guide plate*

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



### ● Packing list

**SMOT**

<b>Packaging list</b>	
Product name	Wired Alarming Strobe light
Qty	100 pcs / box
Carton size	38.3 * 35.3 * 30.3 (cm)
Weight	12Kg



● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair