

Specification	
Product name	Wired Alarming Strobe light
Model	EB-169
Rated voltage	DC12V DC24V
Flashing frequency	90 beats / min
Operating Voltage	9-15VDC 20-28VDC
Light way	LED lights glow
Working current	12V≤80mA / 24V≤100mA
Power lights	2W 5W
Life	≥1000 hours (standard power continuous operation)
size	72 * 42 (mm)



Combination of fixed base plate

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

Strobe indicator light

LED lights, flash frequency up to 90 times a minute.







Strobe Alarming light

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

LED guide plate

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



● Packing list

SMOT

Packaging list	
Product name	Wired Alarming Strobe light
Qty	100 pcs / box
Carton size	38.3 * 35.3 * 30.3 (cm)
Weight	12Kg



● Office

SMQT®



● Exhibitions

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....