

Wired embedded magnetic contact

NC/NO mode optional

35±5(mm) gap distance

Max voltage≤100VDC, Max current≤500mA

Suitable for metal door or window

White/Brown color optional

24g weight

SMQT®



• Parameter

SMQT®

Parameter	
Product name	Emedded magnetic contact sensor
Model	EB-136
Dimension	Φ19 ×25(mm)
Code mode	NO/NC(optional)
Gap	35±5(mm)
Max voltage	≤100V DC
Max current	≤500mA
Max rating	≤10W
Color	Brown/White(optional)
Suit for	Metal door or window
Material	Fireproof ABS housing
Working temperature	-10 °C~50 °C
Net weight	24g

• In-kind shooting

SMQT®



• Feature

SMQT®



EB-136



Dimension: $\Phi 19 \times 25(\text{mm})$

Material: ABS

Max Gap: $\leq 40\text{mm}$

Install way: Drill hole install

Wire : 22# wire 40cm

Power : 0.5A 10W

Fire-proofing materials

Adopt ABS flame retardant material, fire retardant safer, connecting with 22 # wire, total length of 30 cm. Suitable for metal doors and cabinet door, etc.



Waterproof seal

Using imported PC glue sealing, close the magnet and wiring, waterproof, and durable leakage, using more safe and more comfortable



Strong magnetism

Magnetic strength, which can be installed directly drilling, stable performance.



•Packaging & shipping

SMQT®

Packaging list	
Product name	Emedded magnetic contact sensor EB-136
Qty	600 pcs per carton
Carton size	38*30*30(cm)
Weight	16kg



•Office show

SMQT®



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair





2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair