

Product name	Infrared induction door release button
Model	EA-21B
Dimension	EA-21B:86×86×39(mm)
Input voltage	DC 12V
Induction Angle	<115°
Capacity of power	<4W
Induction Distance	10 cm
Contact output	NO/NC/COM
Mechanical test	500.000 times test
Suitable range	Hollow Door
Usage	Access control sysetm and doorphone system
Relative Humidity	0~95%
Environment	-20 °C-50 °C
temprature	
Net weight	EA-21B:0.106kg



Well-made drawing panel,touch feeling is good







Technologyleading anti-interference, induction dustance is adjustable

IN-KIND SHOOTING





SIMILAR PRODUCT



OFFICE SHOW













CUSTOMER













EXHIBITION



CERTIFICATION



HOW TO COOPERATE



PACKAGING & SHIPPING

Detection+Packing+Sealing+Fnishing+International Express



















FAQ

Q: Can I have a sample order?

A:Yes, we are willing to offer trial sample order to you for quality test. Mixed samples are acceptable.

Q: What is the lead time?

A:Sample needs 1-3 working days, mass production time needs 10-15 working days for order less than 5000pcs.

Q: Do you have any MOQ limit?

A:EXW MOQ is 100pcs under blank box.

Q:How do you ship the goods and how long does it take arrive?

A: The sample will be sent to you by optional shipping service (couriers, air, and sea). The delivery time depends on the shipping service.

Q: How will we proceed the order if I have logo to print?

A Firstly, we will prepare artwork for visual confirmation. If the color and position are right, we would make sampling firstly from silk print factory and take picture for your second confirmation before mass production.