

Touch door release button

LED light indication

Touch iduction

Plexiglass panel

2 sizes optional

500000 times mechanical test.

SMQT



• Parameter

SMQT

| Parameter | |
|------------------------|--|
| Product name | LED back light door switch button |
| Model | EA-20 |
| Dimension | Model A:86×56×25(mm) Model B:86×86×25 |
| Input voltage | DC 12V |
| Standard structure | touch Plexiglass |
| Mechanical test | 500,000 times test |
| Suitable range | Hollow Door |
| Color | Black panel, Sliver frame |
| Usage | Access control sysetm and doorphone system |
| Relative Humidity | 0~95% |
| Environment temprature | -20 °C-50 °C |
| Net weight | Model A:0.06kg Model B: 0.09kg |

• Introduction

SMQT





EA-20A



EA-20B

1 Superior Design

Touch push button design simple and beautiful, Panel using organic glass materials, touch induction to open the door, button USES the interactive design of light touch response. Internal using PC rubber production, high temperature resistant do not fade

Resistance to heat shock Organic glass touch responsive



2 Product components

500,000 times test qualified, the relay switch power output, (NO NC COM)3 lines button suitable for all Access control system

NO NC COM, 3 lines

3 Strong stability

Waterproof and dustproof more durable and strong, resistance to high temperature shock do not fade.

Waterproof and Dustproof Stable solid long life



• Application

SMQT®



Switch Power Supply



• Packaging & shipping

SMQT®

| Packaging list | |
|----------------|---|
| Product name | EA-20 LED back light door switch button |
| Qty | 100 pcs per carton |
| Carton size | 37*30*29(cm) |
| Weight | 12kg |



WE LOGISTICS



• Office show

SMQT



• Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....