

Wired metal magnetic contact sensor

NO/NC Code mode optional

50±10(mm) gap distance

Max voltage≤100V DC,Max current≤500mA

Suitable for metal door or window

Material:mode A is Alloy-zn

mode B is ABS

Silver color

Weight:mode A 158g,mode B 62g

SMQT®



• Parameter

SMQT®

Dimensions	106 * 16 * 16 (mm)
connection	Normally open / normally closed
operating distance	50 ± 10 (mm)
Maximum pressure	≤100VDC
load current	≤500mA
working Power	≤10W
housing Material	A zinc alloy B ABS
shape color	silver
scope	Iron door or window
product weight	158g / 62g

• Introduction

SMQT®

The magnetic door contact switch is the magnetic door sensor switch for door access control system and alarm security system.

PRODUCT PICTURE



PRODUCT FEATURE



Wired magnetic contact sensor

NO/NC code mode optional

$50\pm 10(\text{mm})$ gap distance

MAX voltage: $\leq 100\text{V DC}$, MAX current $\leq 500\text{mA}$

Material: mode A:Alloy-zn, mode B:ABS

Suitable for metal door or window

Color:grey silver

Weight: mode A:158g mode B:62g

Welcome OEM and 2 years quality warranty

WHY CHOOSE US ?



1.7 Years golden supplier in Alibaba platform.

2.Our product follow CE standard.

3.Provide 2 years quality warranty.

4.Welcome OEM and ODM.

• *Packaging & shipping*

SMQT[®]



• *Office show*

SMQT[®]



● *Exhibition*

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

