

Wired metal magnetic contact sensor

NO/NC code mode optional

50±10(mm) gap distance

Max voltage ≤100VDC, Max current ≤500mA

Alloy-zn material

Suitable for metal door or window

Grey color

Weight : A:150g B:100g C:50g

SMQT®



• Parameter

SMQT®

Model	EB-138A	EB-138B	EB-138C
Dimensions	46 * 21 * 12 (mm)	47 * 17 * 7 (mm)	30 * 13 * 6 (mm)
Connection	Normally open / normally closed	Normally open / normally closed	Normally open / normally closed
Operating distance	50 ± 10 (mm)	50 ± 10 (mm)	50 ± 10 (mm)
Maximum pressure	≤100VDC	≤100VDC	≤100VDC
Working Power	≤10W	≤10W	≤10W
Housing Material	Zinc Alloy	Zinc Alloy	Zinc Alloy
Scope	Iron door or window	Iron door or window	Iron door or window
Load current	≤500mA	≤500mA	≤500mA
product weight	150g	100g	50g

• Introduction

SMQT®

The magnetic door contact switch is the magnetic door sensor for magnetic door access control system and magnetic door alarm system.

PRODUCT PICTURE



• *Feature*

SMQT

PRODUCT FEATURE



EA-138A

EA-138B

EA-138C

Wired metal magnetic contact sensor

NO/NC code mode optional

50±10 gap distance

Max voltage:≤100V DC, Max current≤500mA

Max rating≤10W

Alloy-Zn material

Suitable for metal door or window

Weight: A:150g B:100g C:50g

Welcome OEM, 2 years quality warranty



• Office show

SMQT®



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair