

NEW

PRODUCT THE ARRIVAL OF THE GOODS

Appearance of the patent, Has the opposite of current protection, Import PC material, heat resistance, corrosion resistance is strong, free manage software, 3 years quality warranty welcome OEM



SMQT®

<https://eis.en.alibaba.com/>

search

THE INTERNATIONAL WEBSITE | ▲

Specification

| | |
|----------------------------|--|
| Product name | 8 tones adjustable 105dB outdoor Fire and emergency use alarm strobe light siren |
| Model | EB-162 |
| Size | 126*120*107(mm) |
| Working voltage | DC 12~30V |
| Alarm current | <40mA(according to working way) |
| Sound pressure | 105db |
| Audio source | 8 tones and light combination (freely adjustable) |
| Ligh flash cycle | <1.3s |
| Working temperature | -20°C~50°C |
| Installation Way | Wall hanging |
| Alarm indicator | Red LED Light |
| Operating humidity | 95%RH |
| Storage temperature | -20°C~60°C |
| Color | Red |
| Weight | 0.4kg |

what features of our EB-162 strobe siren?



1.Wired outdoor emergency flash strobe siren

2.DC 12V~30V power supply

3.Operating current \leq 40mA

4.Sound pressure 105db


5.8 sound and flash light models are adjustable freely

6.2 years warranty , welcome OEM

IN-KIND SHOOTING





HOW TO USE IT



Front




Side



VOLUME



Turn "-" reduce the volume
Turn "+" increase the volume



WATT 100 120 150 200 300

| Code setting | Operating Voltage DC12V, switch "NO" to "g" | | |
|--------------|---|--|-------------|
| Switch 123 | Sound species | Pulse description | DB level |
| LLL/000 | 119 | High level 180uS, low level max:180uS, min:80uS | 116(+/-2db) |
| HHL/110 | Last "di" 0.7hz | High level 85uS, low level 890us | 110(+/-2db) |
| LHL/010 | Sounding "da" | High level 115uS, low level 400us | 114(+/-2db) |
| HLL/100 | High sound 119 | High level 100uS, low level max:1150uS, min:360uS | 115(+/-2db) |
| LHL/011 | Normal 120 | High level 180uS, low level max:2090uS, min:1620us | 116(+/-2db) |
| HLL/101 | High sounding "di" | High level 95uS, low level 930us | 111(+/-2db) |
| LHL/001 | 120 with fast | High level 180uS, low level max:2090uS, min:1620us | 114(+/-2db) |
| HHL/111 | High sound 120 with fast | High level 140uS, low level max:1100uS, min:950us | 116(+/-2db) |

8 Types
Voice & light combination
freely adjustable



Suitable for all kinds of emergency situation!



STANDARD PACKING



SIMILAR PRODUCT

SMQT
铭汗科技



SMQT
铭汗科技



SMQT
铭汗科技



SMQT
铭汗科技



SMQT
铭汗科技



SMQT
铭汗科技



SMQT
铭汗科技



SMQT
铭汗科技




SMQT
铭汗科技



OFFICE SHOW



CUSTOMER



EXHIBITION



CERTIFICATION



HOW TO COOPERATE



PACKAGING & SHIPPING

Detection+Packing+Sealing+Finishing+International Express



Inquiry



Contract



Testing and packing



Receiving



Reply

Receive payment&Product

Delivery



FAQ

Q:Can I have a sample order?

A:Yes, we are willing to offer trial sample order to you for quality test. Mixed samples are acceptable.

Q:What is the lead time?

A:Sample needs 1-3 working days, mass production time needs 10-15 working days.

Q:What is your MOQ?

A:No MOQ limit.

Q:How do you ship the goods and how long does it take arrive?

A:The sample will be sent to you by optional shipping service (couriers, air, and sea),or appointed by buyer,7-15 days.

Q:How will we proceed the order if I have logo to print?

A:Firstly, we will prepare artwork for visual confirmation. If the color and position are right, we would make sampling firstly from silk print factory and take picture for your second confirmation before mass production.