

• Parameter

SMQT

Parameter	
Product name	Wired electric strobe light from alarm strobe light manufacturer
Model	EB-169
Dimension	73ø ×44 (mm)
Working power	12V DC
Operating current	200mA
Contact output	NO/NC
Strobe Speed	68t/m
Color	Red/Bule/Green/Orange(optional)
Suitable for	Fire alarm , Home security
Materials	fireproof ABS hosing
Weight	0.01kg

Introduction

SMQT



• Feature Smot



Strobe Alarming light

- 1. Suitable for higher-end stroboscopic system model.
- 2. Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4. The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

LED guide plate

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



Combination of fixed base plate

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

Strobe indicator light

LED lights, flash frequency up to 90 times a minute.



Packaging list		
Product name	EB-169 Wired electric strobe light from alarm strobe light manufacturer	
Qty	100 pcs per carton	
Carton size	39*30*36(cm)	
Weight	11kg	















• Office show















• Exhibition smot

