

Wired magnetic door contact sensor

NO/NC mode optional

20±5(mm) gap distance

MAX Voltage≤100VDC,MAX current≤500mA

Suitable for wooden door or window

Fireproof ABS shell,White/Brown color optional

Weight10g

SMQT®



• Parameter

SMQT®

Parameter	
Product name	Wired magnetic door sensor
Model	EB-134
Dimension	24×41×6(mm)
Code mode	NO/NC(optional)
Gap	20±5(mm)
Max voltage	≤100V DC
Max current	≤500mA
Max rating	≤10W
Color	Brown/White(optional)
Suit for	wooden door or window
Material	Fireproof ABS housing
Working temperature	-10 °C~50 °C
Net weight	10g

• In-kind shooting

SMQT®



• Feature

SMQT[®]



EB-134

Dimension:24×41×6(mm)

NO/NC mode optional(default is NC mode)

20±5(mm) Gap

MAX voltage≤100VDC,MAX current≤500mA

Suitable for Wooden door or window

Fireproof ABS material shell

White/Brown color optional

Weight 10g

Welcome OEM, 2 years quality warranty

● ***Packaging & shipping***

SMQT

Packaging list	
Product name	EB-134
Qty	1600 pcs per carton
Carton size	38*30*30(cm)
Weight	20kg



• Office show

SMQT



• Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....