



• *Parameter*

SMQT

Especificação	
Nome do Produto	2 vigas outdoor detector perímetro infravermelho
Modelo	ABT-20 ABT-40 ABT-60 ABT-80 ABT-100
Distância	20m 40m 100m 60m 80m (ao ar livre) 60m 120m 180m 240m 300m (indoor)
Tensão operacional	13.8-24vDC 11-18vAC
corrente de operação	40-65mA
velocidade de indução	50-700m / sc
temperatura ambiente	-20 ° C-50 ° C
saída de alarme	NO / NC
saída anti-demolição	NC
ajuste de nível	180 ° (± 90 °)
ajuste vertical	± 10 °
Material	resina de PC

• *Introduction*

SMQT



• *Feature*

SMQT



Sealed integration structure is able to work in the harsh environment
Automatically regulate to confront with fog or inclement weather

Sensitivity (AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built-in integrated optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes, low-power digital

• *Installation*

SMQT



• *Packaging & shipping*

SMQT

lista de embalagem	
Nome do Produto	ABT 2 vigas outdoor detector perímetro infravermelho
Qtde	20 unidades por caixa
tamanho da caixa	51 * 48 * 38 (cm)
Peso	21 kg



• *Office show*

SMQT®



• *Exhibition*

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair