

Converter USB to RS485

Compatible with EIA/TIA RS-232,RS-485 standard

Interface:USB interface

RS-485 interface

Transmission medium:normal cables,twisted-pair cables or shielded cables

57.6kbps in 1200m transmission speed(short distance can reach 230kbps)

Transmission distance:5m(USB port)

1200m(RS485 port)

7-12V input voltage

SMQT



• Parameter

SMQT

Nome do Produto	Conversor USB para RS485
Modelo	EA-02
Dimensão	94 × 35 × 18 (mm)
Característica serial	Interface compatível com EIA / TIA RS-232C, padrão RS-485
Interface Elétrica	Porta USB, conector fêmea DB9, lado RS-485, conector DB9 macho com terminal (cinco fios).
Maneira de trabalhar	Semi-duplex assíncrono
Transmissão média	Linha comum, par trançado ou cabo blindado
Taxa de transmissão	Até 57.6kbps (perto da taxa de 230kbps) na distância de 1200m
Distância de transmissão	5 m (extremidade USB) 1200 m (terminal RS-485)
Cor	cinzento
Uso	Sistema de controle de acesso
Humidade relativa	5% ~ 95%
Temperatura ambiente	-10 °C ~ 85 °C
carta de acordo	Transparente
Peso líquido	0,116 kg

• Introduction

SMQT

USB para conversor RS485 para o software do sistema de controle de acesso de porta operar no computador.



• *Feature*

SMQT



Converter USB to RS485
Interface compatible with EIA
/ TIA RS-232C, RS-485 standard

Electrical Interface:

USB port, DB9 female connector
RS-485 side, DB9 male connector

Transmission rate:

Up to 57.6kbps (close up to 230kbps
rate) in the 1200m distance

Transmission distance:

5 m (USB end) 1200 m (RS-485 terminal)

Suitable for data transmission system

0.116kg weight

Welcome OEM and 2 years quality warranty

switch power supply



Door release button



Access control keypad

Converter USB to RS485 EA-02



PC

• Office show

SMQT®



• Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....