

Wired metal magnetic contact sensor

NO/NC Code mode optional

50±10(mm) gap distance

Max voltage≤100V DC,Max current≤500mA

Suitable for metal door or window

Material:mode A is Alloy-zn

mode B is ABS

Silver color

Weight:mode A 158g,mode B 62g

SMQT



• Parameter

SMQT

| | |
|------------------------|--|
| Dimensões | 106 * 16 * 16 (mm) |
| conexão | Normalmente aberto / normalmente fechado |
| Distância de operação | 50 ± 10 (mm) |
| Pressão máxima | ≤ 100VDC |
| Corrente de carga | ≤500mA |
| Poder de trabalho | ≤ 10W |
| Material de alojamento | Uma liga de zinco B ABS |
| Cor da forma | prata |
| escopo | Ferro porta ou janela |
| Peso do Produto | 158 g / 62 g |

• Introduction

SMQT

O interruptor magnético do contato da porta é o interruptor magnético do sensor da porta para o sistema de controle do acesso da porta eo sistema de segurança do alarme.

PRODUCT PICTURE



PRODUCT FEATURE



Wired magnetic contact sensor

NO/NC code mode optional

50±10(mm) gap distance

MAX voltage: ≤100V DC, MAX current ≤500mA

Material: mode A: Alloy-zn, mode B: ABS

Suitable for metal door or window

Color: grey silver

Weight: mode A: 158g mode B: 62g

Welcome OEM and 2 years quality warranty

WHY CHOOSE US ?



1.7 Years golden supplier in Alibaba platform.

2.Our product follow CE standard.

3.Provide 2 years quality warranty.

4.Welcome OEM and ODM.





● Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....