Parameter

SMQT

Parâmetro	
Nome	ID de tela OLED (125Khz) Leitor de cartão de controle de acesso
Modelo	EA-93K
Dimensão	96 × 96 × 22 (mm)
Tensão de trabalho	12V ± 3VDC
Poder de lavagem	& Lt; 1w
Tipo de carta	IC de 13,56 MHz
Distância de indução	60mm
Distância do cabo	150m
Formato de comunicação	WG26 / WG34
Taxa de transmissão	1bit / ms
Saída do teclado	4bit / 8bit
Cor	Preto / Branco (opcional)
Material de invólucro	PC
Adequado para	Sistema de controle de acesso do escritório em casa
Temperatura ambiente	-30 ℃ ~ 65 ℃
Peso líquido	0,2 kg

EA-93K

Waterproof keypad IC(13.56Mhz) wiegand card reader

IC(13.56Mhz) card type

Wiegand 26/34 communication(optional)

Waterproof,IP66 level

Laser carving and wear-resisting keyboard

Short-circuit and lightning protection

Tamper device

Plug type connection,easy to install

2 years warranty,welcome OEM

In-kind shooting

•*Installation*

SMQT



•Packaging & shipping

SMQT

Lista de embalagens	
Nome do Produto	Impermeável (cartão IC de 13,56 MHz) Leitor de cartão de controle de acesso EA-93K
Qtd	36 pcs por cartão
Tamanho da caixa	45 * 32 * 32 (cm)
Peso	9kg

•Office show

SMQT

•*Exhibition*

SMQT