Parameter

SMQT

□□□□	
□□□□□□□□□□□□□	2 □□
□□□	ABT-20 ABT-40 ABT-60 ABT-80 ABT-100
□□□□□□□	20m 40m 60m 80m 100m (□□□□□□□□) 60m 120m 180m 240m 300 □□□□ (□□□□□□)
□□□□□□□□□□□□□□□□□□□□□□	13.8-24vDC 11-18vAC
□□□□□□□□□□□□□□□□□□□□□	40-65mA
□□□□□□□□□□□□□□□□□□□□□□□	50-700m / SC
□□□□□□□□□□□□□□□□□□□□□□□	-20 ° C-50 ° C
□□□□□□□□□□□□□□□□□□	NO / NC
□□□□□□□□□□□□□□□□□□□□□□□□□□	□□□□□□□□□□□□
□□□□□□□□□□□□	180 ° (± 90 °)
□□□□□□□□□□□	± 10 °
□□□□□	□□□□□□□□□

Introduction

SMQT

POWER
ACTIVE INFRARED SENSOR
Transmit

GOOD
LEVEL
PLASH
ACTIVE INFRARED SENSOR
Receive

ABT-30
POWER
ACTIVE INFRARED SEN
Transmit

ACTIVE INFRARED SENS

ABT-30
POWER
ACTIVE INFRARED SEN
Transmit

1 2 3 4 5 6 7
POWER
FREE
AMC-219-48
6 7
TAMPER

•*Feature*

Sealed integration structure is able to work inthe has enviroment

Automtically regulate to confranted with fog or inclement weathe

Sensitivity(AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built -in integrate optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes,low-power digital

•*Installation*

SMQT

Packaging & shipping

[illegible]	
[illegible]	ABT 2 [illegible]
[illegible]	20 [illegible]
[illegible]	48 * 51 * 38 ([illegible].)
[illegible]	21kg

• *Office show*

SMQT

• *Exhibition*

SMQT

2011 Brazil Fair
2012 Shenyang Fair
2013 Jinan Fair
2013 Shenzhen Fair
共赢
.....
2012 Shenyang Fair
2013 Shenyang Fair
2013 Shenzhen Fair
2015 Shenzhen Fair