



## ● Parameter

SMQT®

□□□□	
□□□□□□□□□□	2 □□□
□□□	ABT-20 ABT-40 ABT-60 ABT-80 ABT-100
□□□□□□□□	20m 40m 60m 80m 100m (□□□□□□□□) 60m 120m 180m 240m 300 □□□□ (□□□□□□)
□□□□□□□□□□□□□□□□	13.8-24vDC 11-18vAC
□□□□□□□□□□□□□□□□	40-65mA
□□□□□□□□□□□□□□□□	50-700m / SC
□□□□□□□□□□□□□□□□	-20 ° C-50 ° C
□□□□□□□□□□□□□□□□	NO / NC
□□□□□□□□□□□□□□□□□□□□	□□
□□□□□□□□□□□□□□□□□□□□	180 ° (± 90 °)
□□□□□□□□□□□□□□□□□□□□	± 10 °
□□□□□□	□□□□□□□□□□

## ● Introduction

SMQT®



• *Feature*

**SMQT**



Sealed integration structure is able to work in the harsh environment

Automatically regulate to confront with fog or inclement weather

Sensitivity (AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built-in integrate optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes, low-power digital

---

## • *Installation*

**SMQT**





## • Office show

SMQT®



## • Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....