



□□□□□□□□□□□□:	□□□□□□□□□□□□□□□□□□□□ 3A 36V DC □□□□□□□□□□□□□□
□□□□:	86 * 86 * 20mm
□□□□□□□□□□□□□□:	□□□□□□□□□□
□□□□□□□□□□□□:	3A @ 36VDC □□□□□□
□□□□□□□□□□□□:	NC \ NO \ COM
□□□□□□□□□□□□:	100000 □□□□□□
□□□□□□□□□□□□□□:	□□□□□□□□□□
□□□□□□□□□□□□□□□□:	-10 ~ + 55 ° C (14-131F)
□□□□□□□□:	□□□□□□□□□□
□□□□□□□□:	0.15kg

□□□□□□□□□□□□ **EA-26A / B / C** □□□□□□?



1. Plastic door release button for access control system

2. 100,000 times mechanical test

3. Fireproof ABS material panel

4. 3 models appearance optional

5. 2 years warranty, welcome OEM

IN-KIND



□□□□□□□□□□□□□□□□



Switch power supply



Door release
button EA-26



Standalone
controller

Converter
(RS232 to RS485)



PC

□□□□□□□□□□□□□□□□



OFFICE SHOW



□□□□□



□□□□□□□□

2011 Brazil Fair



2012 shen yang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 shen yang Fair



2013 shen yang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair





PACKAGING & SHIPPING

Detection+Packing+Sealing+Finishing+International Express



XXXXXXXXXXXXXXXXXXXX

0000: XX?

