

Parameter

SMQT

□□□□□□□□□□□□	
□□□□□□□□□□□□□□	DC 12V 5A □□□
□□□	EA-38B
□□□□	205 × 165 × 74 (mm)
□□□□□□□□□□□□□□□□□□	AC220V
□□□□□□□□□□□□□□□□□□□□□□□□	50Hz
□□□□□□□□□□□□	12V DC
ouput □□□□□□□□	5A
□□□□□□□□□□□□□	60W
□□□□□□□□□□□	Built-in □□□□□□□□□□□□□□□□□□□□□□□□□ circut □□□□□□□□ interernce
□□□□□□□□□□□□	0 ~ 15 □□□□□□□
□□□□□□□□□□□□□□□	□□□□□□□□□□□□□ PC □□□□□□□□□□ □□□□□□□□□□□□□□□ □□□□□ □□□□□□□
□□	□□□
□□□□□□□□□	sysetm □□□□□□□□□□□□□□□□□□□□□□□□□ doorphone
temprature □□□□□□□□□□□□	-20 ℃ ~ 61 ℃
□□□□□□□□□□□□□	2.5 □□
optionals	□□□□□□ □□□□□□□□□□ (□□□□□□□□□□□□□□ 80 □□□□□□□□□□□□□□□□□) □□□□□□□□□□□□□□□ □□□□□□□□□□ (12V 7AH)

Introduction

SMQT







•*Feature*

SMQT



Access control switch power supply
AC 220V input,DC 12V 5A output
0~15s time relay
Double face PC board,
pure copper transformer,steel shell
Short circuit protection Anti-interference
Suitabel for access control system,
Doorphone system
Remote control function and
backup battery optional
2 years warranty, welcome OEM

Application



Packaging & shipping

[illegible]	
[illegible]	EA-38B DC 12V 5A [illegible]
[illegible]	10 [illegible]
[illegible]	42 * 50 * 27 ([illegible].)
[illegible]	25kg

• *Office show*

SMQT

• *Exhibition*

SMQT

2011 Brazil Fair
2012 Shenyang Fair
2013 Jinan Fair
2013 Shenzhen Fair
共赢
.....
2012 Shenyang Fair
2013 Shenyang Fair
2013 Shenzhen Fair
2015 Shenzhen Fair