

● Parameter



Interface	EIA / TIA RS-232, RS-485
Connector	USB, DB9, RS-485 (Terminal)
Transfer Rate	57.6Kbps (max 230 baud)
Length	1200m
Power	5V (USB), 1,200V (RS-485 Terminal)

● Introduction



This is a USB to RS485 converter. It can be used to connect a USB to RS485. It is compatible with Windows. The converter is a USB to RS485 converter.

RS485 USB

ASIC USB

RS-485 7V ~ + 12V

Windows 98 / Me Windows 2000 / XP

MAC Linux v5.0

USB v1.1 USB v1.1 CDC

USB

USB

57.6Kbps 1200 baud (max 230 baud)

TIA / EIA RS-485

32 485

(RS-485 32 485)

● Dimension Picture



● Installations



**Switch Power supply**



**Door release button**



**Standalone Access controller**



**PC**

**Converter(USB to RS 485)**

EA-02



**● Features**



ASIC) USB  
 / 2.0  
 460,800  
 Built-in 128 TX / RX 512  
 Mac  
 Win95 / 98 / 98SE / ME / 2000 / XP / NT3.5  
 USB  
 Mac

**● Packing list**



100 /	
53L ***** 40W 36.5H (.)	

□□□□□□□□□□

8.88Kg

● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....