

● Parameter



□□□□□□□□□□□□	
□□□□□□□□□□	□□ LED □□□□ □□□□□□□□
□□□□	EA-27
□□□□	86 L * 86W * 20H (mm)
□□□□□□	□□□□□□ 3A □□□□□□□□□□□□ 36VDC 12VDC □□□□
□□□□□□□□□□□□□□□□	□□□□□□□□□□ □□□□□□□□
□□□□□□□□□□□□	□□□□□ / NC / COM □□□□□□
□□□□□□□□□□□□□□□□	□□□□ 500,000 □□□□□□□□□□□□□□
□□□□□□□□□□□□□	□□□□□□□□□□□□□□□□□□□□
□□□□□□□□	-10 °C ~ + 50 °C
□□□□□□□□□□	0-95% (□□□□□□□□□□□□□□□□□)
□□□□□□□□□□	□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□	0.09 □□□□□□□□□
□□□□□□□	100 / □□□□□□

● Introduction



□□□□□□□□□□□□□□□□□□□□□□□□ LED □□□□□□□□□□□□  
 □□  
 □□  
 □□  
 □□  
 □□  
 □□

● Dimesion Picture



● Installations

SMQT

Switch Power supply



Door release  
button EA-27



Converter  
(RS232 to RS485)



Standalone  
controller



PC

● Features

SMQT



THE ONE  
***Strong stability***

PC rubber seal lock core,  
resistance to heat shock,  
500, 000 times mechanical test  
qualified, suitable for all  
Access control system



THE SECOND  
***Superior Design***

Simple and beautiful appearance,  
stainless steel wire drawing  
panel.

● Packing list

**SMQT**

□□□□□□□□□□□□□□□□	
□□□□□□□□□□	□□□□□ LED □□□□□□□□□□□□□□
□□□□□□	100 / □□□□□
□□□□□□□□□□□□	46.5 L * 37.5W * 28 H (cm)
□□□□□□□□□□□□□□□□	10.1 □□.





● In the Office

SMQT®



● Exhibitions

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair