

RFID Model	EA-82K (EPC Gen2 Class1 Gen2)
Power Supply	DC12V ± DC3V
Power Consumption	< 2W
Frequency	125KHz ID
Dimensions	60mm
Capacity	10000
Memory	10000
Interface	RS485
Transmission Rate	9600bps (N, 8,1)
Memory Type	4MbitsFLASHMemory
Dimensions	96L ***** 96W 22H (mm)
Operating Temperature	0°C
Storage Temperature	-30 °C ~ + 65 °C
Identification	RFID/UID + Card + Password/Access Code

The SMQT RFID module supports TCP / IP, RS485 and other connection software. It is a high-performance RFID module that can be used in various applications.

* The module is designed for industrial use (high temperature, high humidity, etc.)

*

The module is designed for industrial use; it is suitable for applications such as breathing background light and Takeout.

*

The module is designed for industrial use; it is suitable for applications such as breathing background light and Takeout.

* The module is designed for industrial use, it is suitable for applications such as breathing background light and Takeout.

The module is designed for industrial use; it is suitable for applications such as breathing background light and Takeout.

* The module is designed for industrial use, it is suitable for applications such as breathing background light and Takeout.

The module is designed for industrial use; it is suitable for applications such as breathing background light and Takeout.

The module is designed for industrial use; it is suitable for applications such as breathing background light and Takeout.



● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....