Parameter

□□□□□□□□□□□□□□□□□□□□	DC12V
□□□□□□□□□□□□□□□□□□□□□□	15W
□□□□□□□□□□□□□	□□□□□□□□□□ ABS
□□□□□□□□□□□□□□□□□	800HZ ~ 15KHZ
SNR	≥82db
□□□□□□□□□□□□□□□□	150db
□□□□□□□□□□□□□□□□□□	-10 ℃ ~ 65 ℃
□□□□□□□□	40% □□□ 95%

Introduction

NV020S
□□;
□□□□□ ABS □□□□□□□□□□□□□□□□□□□□□□□□□□, □□□□□□□□□□□□□□□□□□□□□□□□, □□□□□, □□□□□□□□□□□□□□□□□;
Built-in □□□□□□□□□□□□□□ Philips □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□, □□;
□□□□□□: □□ □
□□
□

Dimesion Picture

Features

SMQT

1

Fire-proofing materials

Fire—proofing materials

High-strength fire retardant ABS material, the surface spray processing, durable, long service life .

2

Alarm sounds great

Alarm sounds great

NV020S do use voice chip voice processing core, with industrial-grade performance and stability of the reticle;

Built-in dual output Philips audio amplifiers, loud, high definition .

3

Rotating stents

Rotating stents

Single power supply, effective utilization of power usage.

It can set on the floor or wall, 90' Rotating stents.

4

Wide applicability

Wide applicability

High-strength fire retardant ABS material, the surface spray processing, Scope: oil, high pressure, mines, toxic, airport bird and so on.

Packing list

SMQT

□□□□□	50 / □□□□□
□□□□□□□□□□□□□□□□□	57 * 57 * 23.5 (□□.)
□□□□□□□□□□□□	16.46Kg

Office

SMQT

Exhibitions

SMQT