

● Parameter

SMQT

項目	
項目名稱	項目說明
型號	EB-169
適用電壓	DC12V DC24V
閃爍次數	90 次 / 分鐘
適用電壓範圍	9-15VDC 20-28VDC
燈珠	LED 燈珠
燈珠功率	12V≤80mA / 24V≤100mA
燈珠數量	2W 5W
壽命	≥ 1,000 小時 (平均壽命)
尺寸	72 * 42 (mm)

● Introduction

SMQT



Combination of fixed base plate

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

Strobe indicator light

LED lights, flash frequency up to 90 times a minute.







Strobe Alarming light

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

LED guide plate

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



● Packing list

SMOT®

产品名称	
产品名称	产品名称 S trobe
数量	100 个 / 个
尺寸	38.3 * 35.3 * 30.3 (mm.)
重量	12kg



● Office

SMQT®



● Exhibitions

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....