

Touch door release button

LED light indication

Touch iduction

Plexiglass panel

2 sizes optional

500000 times mechanical test.



• Parameter



品名	触摸门铃
产品型号	EA-20
规格	规格 A: 86 × 56 × 25 (mm) 规格 B: 86 × 86 × 25
供电电压	DC 12V
面板材质	Plexiglass
使用寿命	500,000 次
安装方式	表面安装
适用环境	室内、室外
系统兼容性	支持 sysetm 门铃系统、门铃系统 doorphone 系统
湿度	0 ~ 95%
temperature 工作温度	-20 °C -50 °C
重量	规格 A: 0.06kg 规格 B: 0.09kg

• Introduction







EA-20A



EA-20B

1 Superior Design

Touch push button design simple and beautiful, Panel using organic glass materials, touch induction to open the door, button USES the interactive design of light touch response. Internal using PC rubber production, high temperature resistant do not fade

Resistance to heat shock Organic glass touch responsive



2 Product components

500,000 times test qualified, the relay switch power output, (NO NC COM)3 lines button suitable for all Access control system

NO NC COM, 3 lines

3 Strong stability

Waterproof and dustproof more durable and strong, resistance to high temperature shock do not fade.

Waterproof and Dustproof Stable solid long life



Application

SMQT



Switch Power Supply



Touch Induction Door Release button EA-20

Single Door Access control Keypad

Packaging & shipping

SMQT

	□□□□□□□□□□□□□□
□□□□□□□□□□□□	EA-20 □□□□□□□□ LED □□□□□□□□□□□□
□□□□□	100 □□□□□□□□□□□□
□□□□□□□□	37 * 30 * 29 (mm.)
□□□□□□□	12kg



WE LOGISTICS



• Office show

SMQT



• Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair