

Wiegand 26 SM7 CPU
13.56MHz Triple Recognition Fuction



参数	
名称:	Wiegand 26 SM7 CPU 13.56MHz Triple Recognition Fuction
尺寸:	96mm * 96mm * 22mm
工作电压:	9VDC-16VDC
工作电流:	≤ 120mA
工作频率:	13.56MHz
读卡距离:	& lt; 0.1 (读卡距离)
读卡类型:	Wiegand26
厚度:	3.5cm-5.5cm
重量:	& lt; 100 g
接口:	
供电:	± 15v
工作温度:	0 °C ~ 60 °C
存储温度:	-20 °C ~ 70 °C

☐☐☐☐☐☐☐☐☐☐ Wiegand 13.56MHz CPU Card Reader ☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐?



Support CPU SHC1112 card

Support the ISO14443a protocol

Card number and key can be user-defined

Fully sealed design epoxy seal and waterproof type

Wiegand 26 communication interface,26-122 bit output

☐☐☐☐☐☐☐☐☐☐ IN-KIND




□□□□□□□□□□□□□□

CPU Card Reader



GND	9-16V DC	D0	D1	Buzzer	LED	RS232-TX	RS232-RX
-----	----------	----	----	--------	-----	----------	----------

Can work with different access control accessories :



Power Supply



EM Lock



Bluetooth Door Button



Dual Doors Access Control



□□□□□□□□

SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



SMQT[®]
铭汗科技



OFFICE SHOW



□□□□□



□□□□□□□□

2011 Brazil Fair



2012 shen yang Fair




2013 Jinan Fair



2013 Shenzhen Fair



2017 Shenzhen Fair



2012 shen yang Fair



2013 shen yang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair





QUESTION

QUESTION

[illegible]

-3

A: 請問貴公司 目前 **MOQ** 請問是怎麼計算的? 是依照數量還是金額?

問: 請問貴公司目前是否有提供 1610 的規格? 還是只有 1615 的規格?

問: 請問貴公司目前是否有提供 1610 的規格? 還是只有 1615 的規格?
(請問貴公司目前是否有提供 1610 的規格? 還是只有 1615 的規格?) 請問貴公司目前是否有提供 1610 的規格? 還是只有 1615 的規格? **7-15** 請問

問: 請問貴公司目前是否有提供 1610 的規格? 還是只有 1615 的規格?

問: 請問貴公司目前是否有提供 1610 的規格? 還是只有 1615 的規格?
請問貴公司目前是否有提供 1610 的規格? 還是只有 1615 的規格?
請問貴公司目前是否有提供 1610 的規格? 還是只有 1615 的規格?