

Wired magnetic contact sensor

NC/NO code mode optional
20±5(mm) gap distance
MAX voltage≤100V DC,MAX current≤500mA
Suitable for wooden door or window
Fireproof ABS material shell
White/Brown color optional
8g weight



XXXXXXXXXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXXXX	
XXXXXXXXXXXXXXXXXXXX	XXXXXXXXXXXXXXXXXXXX / XXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXX
XXX	EB-135
XXXX	24 × 41 × 6 (mm)
XXXXXXXX	NO / NC (XXXXXXXXXXXX)
XXXXXXXX	20 ± 5 (mm)
XXXXXXXXXXXXXXXXXXXX	≤ 100V DC
XXXXXXXXXXXXXXXXXXXX	≤500mA
XXXXXXXXXXXX	≤10W
XX	XXXXXXXX / XXX (XXXXXXXXXXXX)
XXXXXXXXXXXX	XXXXXXXXXXXXXXXXXXXX
XXXXXX	XXXXXXXXXXXXXXXXXXXX ABS
XXXXXXXXXXXXXXXXXXXX	-10 °C ~ 50 °C
XXXXXXXXXXXX	8g



EB-135

2 Color optional



White

Brown

Fireproof ABS housing

Brown or White color optional

Suit for wooden doors or windows

Normal open or Normal close optional

2 years quality warranty,welcome OEM

100

□□□□□□□□ **IN-KIND**





(Notice:need match the home align system to



In window close status, door magnetic host and magnetic stripe respectively embedded in the two Windows, do not to leave a gap between, open the window after the success of alarming, Then to fixed.



Sliding window



In window close status, door magnetic host and magnetic stripe respectively embedded in the two Windows, do not to leave a gap between, open the window after the success of alarming, Then to fixed.

White



Brown





SHOW CASE



□□□□□□ □□□□□□

OFFICE SHOW



□□□□□□



□□□□□□□□

2011 Brazil Fair



2012 shen yang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 shen yang Fair



2013 shen yang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



