



• Parameter

SMQT®

şartname	
Ürün adı	2 adet açık kızılötesi çevre dedektörü girişler
model	ABT-20 ABT-40 ABT-60 ABT-80 ABT-100
Mesafe	20m 40m 60m 80m 100m (dış mekan) 60m 120m 180m 240m 300m (kapalı)
Çalışma gerilimi	13.8-24vDC 11-18vAC
işletim akımı	40-65mA
indüksiyon hız	50-700m / sc
Çevre sıcaklığı	-20 ° C-50 ° C
alarm çıkışı	NO / NC
Anti-yıkım çıktı	NC
Seviye ayarı	180 ° (± 90 °)
dikey ayarlama	10 ° ±
Malzeme	PC reçine

• Introduction

SMQT®



• Feature

SMQT



Sealed integration structure is able to work in the harsh environment

Automatically regulate to confront with fog or inclement weather

Sensitivity (AGC circuit)

easily adjust and calibrate the horizontal/vertical optional angle

Built-in integrate optical telescopes, anti-jamming jacket

Anti-lighting circuit designed

High-power infrared receiver on the tubes, low-power digital

● *Installation*

SMQT[®]



• *Packaging & shipping*

SMQT

Ambalaj listesi	
Ürün adı	ABT 2 adet açık kızılötesi çevre dedektörü kirişler
Adet	karton başına 20 adet
Karton boyutu	51 * 48 * 38 (cm)
Ağırlık	21kg



• Office show

SMQT



• Exhibition

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair



.....