

Converter USB to RS485

Compatible with EIA/TIA RS-232, RS-485 standard

Interface: USB interface

RS-485 interface

Transmission medium: normal cables, twisted-pair cables or shielded cables

57.6kbps in 1200m transmission speed (short distance can reach 230kbps)

Transmission distance: 5m (USB port)

1200m (RS485 port)

7-12V input voltage

SMQT®



• Parameter

SMQT®

Ürün adı	USB'den RS485'e Dönüştürücü
Model	EA-02
Boyut	94 × 35 × 18 (mm)
Seri özellik	EIA / TIA RS-232C, RS-485 standardıyla uyumlu arayüz
Elektrik Arayüzü	USB portu, DB9 dişi konnektör, RS-485 tarafı, terminalli DB9 erkek konnektör (beş telli).
Çalışma yolu	Eşzamansız yarı dubleks
İletim ortamı	Normal hat, bükülmüş çifti veya ekranlanmış kablo
Aktarım hızı	1200m mesafede 57.6kbps'ye kadar (230kbps hızına yakın)
İletim mesafesi	5 m (USB bitişi) 1200 m (RS-485 terminali)
Renk	gri
Kullanımı	Giriş kontrol sistemi
Bağıl nem	% 5 - % 95
Ortam sıcaklığı	-10 °C ~ 85 °C
anlaşma mektubu	Şeffaf
Net ağırlık	0.116kg

• Introduction

SMQT®

Kapı erişim kontrol sistemi yazılımı için USB'den RS485'e çevirici bilgisayarda çalışır.



• *Feature*

SMQT



Converter USB to RS485
Interface compatible with EIA
/ TIA RS-232C, RS-485 standard

Electrical Interface:

USB port, DB9 female connector
RS-485 side, DB9 male connector

Transmission rate:

Up to 57.6kbps (close up to 230kbps
rate) in the 1200m distance

Transmission distance:

5 m (USB end) 1200 m (RS-485 terminal)

Suitable for data transmission system

0.116kg weight

Welcome OEM and 2 years quality warranty

switch power supply



Door release button



Access control keypad

Converter USB to RS485 EA-02



PC

• Office show

SMQT®



• Exhibition

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

