

● Parameter

SMQT®

Ürün boyutu	86L * 86W * 39h (mm)
Giriş gerilimi	DC12V
Kontak çıkışı	NO / NC / COM
dayanıklılık testi	500.000 kez test yaşlanma
Tip	dar kapı çerçevelerinin çeşitli
Sıcaklık	-20 °C ~ + 50 °C
uygulanabilir nem	% 0 ila 95 (nispi nem)
algılama mesafesi	10cm
Adet	100

● Introduction

SMQT®

- Kızılötesi optik teknoloji
 - IP-55 sınıfı koruma düzeyi / SUS 304 paslanmaz çelik levha
 - Bulaşıcı hastalıkların yayılması Karşı (sağlığın korunması)
 - Röle anahtarı çıkışı
- Çift LED göstergesi sensörü bekleme ya da yakın
- 1) Sensör Bekleme: Mavi ışık yayan diyotlar, mavi ışıklar
 - 2) 10 cm sensöre erişimi sağlamak, kırmızı ışık
- Endüstriyel Koruma seviyesi (su geçirmez, toz geçirmez): IP-55
 - İletişim Rating: 3A / 120V AC, 30V DC
 - Çalışma voltajı: DC 12V
- Çalışma sıcaklığı aralığı: 20-55 °C
- Ömür: 100000 kez
- Ağırlık: 85 g
- erişim kontrolü kapı açma düğmesi paslanmaz çelik itme çıkış düğmesi bulunur.

● Dimesion Picture

SMQT®



● Installations

SMQT



● Features

SMQT

1 Durable and Reliable
more than 5 years life time

2 Well-made
drawing panel, touch feeling is extraordinary

4 Installation
easy install



3 Welcome OEM
print logo

5 Technology-leading
Anti-interference, induction distance is adjustable



Adet	100 / kutu
Ambalaj Özellikleri	46.5L * 37.5W * 28H (cm)
Ambalaj ağırlığı	10.6Kg

● Office

SMQT®



● Exhibitions

SMQT®

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....

2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

