

● Parameter

SMQT®

Çalışma gerilimi	DC12V
Nominal çıkış gücü	15W
Ev materyalleri	ABS yangın geciktirici malzemeler
Frekans tepkisi	800HZ ~ 15KHZ
SNR	≥82db
Çıkış ses yüksekliği	150db
Çalışma sıcaklığı	-10 °C ~ 65 °C
Nem	% 40 -% 95

● Introduction

SMQT®

NV020S, endüstriyel sınıf performans ve retikül stabilitesi ile ses yongası ses işleme çekirdeği kullanır;

Yüksek mukavemetli yangın geciktirici ABS malzeme, yüzey sprej işleme, dayanıklı, uzun hizmet ömrü;

Dahili çift çıkışlı Philips ses amplifikatörleri, yüksek, yüksek çözünürlük;

Tek güç kaynağı, güç kullanımının etkin kullanımı;

Kapsam: yağ, yüksek basınç, mayın, toksik, havaalanı kuş vb.

Elektronik siren, yangın alarmı ve antif alarm ile kullanılan alarm siren 115db'dir.

● Dimesion Picture

SMQT®





1

Fire-proofing materials

Fire-proofing materials

High-strength fire retardant ABS material, the surface spray processing, durable, long service life.



2

Alarm sounds great

Alarm sounds great

NV020S do use voice chip voice processing core, with industrial-grade performance and stability of the reticle;

Built-in dual output Philips audio amplifiers, loud, high definition.



3

Rotating stents

Rotating stents

Single power supply,
effective utilization of
power usage.

It can set on the
floor or wall, 90°
Rotating stents.



4

Wide applicability

Wide applicability

High-strength fire retardant ABS
material, the surface spray
processing, Scope: oil, high
pressure, mines, toxic, airport
bird and so on.

● Packing list

SMOT

Adet	50 / kutu
Ambalaj Özellikleri	57 * 57 * 23,5 (cm)
Ambalaj ağırlığı	16.46Kg



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....