

● Parameter

SMQT

Şartname	
Ürün adı	Kablolu Alarm Strobe ışığı
model	EB-169
Anma gerilimi	DC12V DC24V
Yanıp sönen frekans	90 vuruş / dk
Çalışma gerilimi	9-15VDC 20-28VDC
Işık yolu	LED ışıklar yanıyor
Çalışma akımı	12V≤80mA / 24V≤100mA
Güç ışıkları	2W 5W
hayat	Hours1000 saat (standart güç sürekli çalışma)
boyut	72 * 42 (mm)

● Introduction

SMQT



Combination of fixed base plate

Base plate is divided into two pieces, shape material are exactly the same.

Also can use double post stent paste on the wall.

Strobe indicator light

LED lights, flash frequency up to 90 times a minute.







Strobe Alarming light

- 1.Suitable for higher-end stroboscopic system model.
- 2.Chimney texture design improves the light diffusion effect.
- 3.Flash 90 times per minute.
- 4.The high-quality LED light.
- 5.IP44 protection grade.
- 6.AS+ABS shell.

LED guide plate

Select high-quality materials, strict quality control, production of exquisite workmanship. This assures the mixer durable products.



● Packing list

SMOT

Paketleme listesi	
Ürün adı	Kablolu Alarm Ssorum ışığı
Adet	100 adet / kutu
Karton boyutu	38,3 * 35,3 * 30,3 (cm)
Ağırlık	12kg



● Office

SMQT



● Exhibitions

SMQT

2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair

.....