

Wired metal magnetic contact sensor

NO/NC code mode optional

50±10(mm) gap distance

Max voltage ≤100VDC, Max current ≤500mA

Alloy-zn material

Suitable for metal door or window

Grey color

Weight : A:150g B:100g C:50g

SMQT®



• Parameter

SMQT®

Model	EB-138A	EB-138B	EB-138C
Boyutlar	46 * 21 * 12 (mm)	47 * 17 * 7 (mm)	30 * 13 * 6 (mm)
Bağ	Normalde açık / normalde kapalı	Normalde açık / normalde kapalı	Normalde açık / normalde kapalı
Çalışma mesafesi	50 ± 10 (mm)	50 ± 10 (mm)	50 ± 10 (mm)
Maksimum basınç	≤100VDC	≤100VDC	≤100VDC
Çalışma Gücü	≤10W	≤10W	≤10W
Ev materyalleri	Çinko Alaşım	Çinko Alaşım	Çinko Alaşım
Kapsam	Ütü kapı veya pencere	Ütü kapı veya pencere	Ütü kapı veya pencere
Yük akımı	≤500mA	≤500mA	≤500mA
Ürün ağırlığı	150 gr	100 gram	50 gram

• Introduction

SMQT®

Manyetik kapı kontak anahtarı, manyetik kapı erişim kontrol sistemi ve manyetik kapı alarm sistemi için manyetik kapı sensörüdür.

PRODUCT PICTURE



• *Feature*

SMQT

PRODUCT FEATURE



EA-138A

EA-138B

EA-138C

Wired metal magnetic contact sensor

NO/NC code mode optional

50±10 gap distance

Max voltage:≤100V DC, Max current≤500mA

Max rating≤10W

Alloy-Zn material

Suitable for metal door or window

Weight: A:150g B:100g C:50g

Welcome OEM, 2 years quality warranty



• Office show

SMQT[®]



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair



.....



2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair