

Wired embedded magnetic contact

NC/NO mode optional

35±5(mm) gap distance

Max voltage≤100VDC, Max current≤500mA

Suitable for metal door or window

White/Brown color optional

24g weight

SMQT®



• Parameter

SMQT®

Tham số	
Tên sản phẩm	cảm biến tiếp xúc từ Emedded
Mô hình	EB-136
Chiều hướng	Φ19 × 25 (mm)
chế độ Mã	NO / NC (tùy chọn)
Lỗ hồng	35 ± 5 (mm)
điện áp Max	≤100V DC
Max hiện tại	≤500mA
giá Max	≤10W
Màu	Brown / White (tùy chọn)
Phù hợp cho	cửa kim loại hoặc cửa sổ
Vật chất	nhà ở ABS chống cháy
Nhiệt độ làm việc	-10 °C ~ 50 °C
Khối lượng tịnh	24g

• In-kind shooting

SMQT®



• Feature

SMQT®



EB-136



Dimension: $\Phi 19 \times 25(\text{mm})$

Material: ABS

Max Gap: $\leq 40\text{mm}$

Install way: Drill hole install

Wire : 22# wire 40cm

Power : 0.5A 10W

Fire-proofing materials

Adopt ABS flame retardant material, fire retardant safer, connecting with 22 # wire, total length of 30 cm. Suitable for metal doors and cabinet door, etc.



Waterproof seal

Using imported PC glue sealing, close the magnet and wiring, waterproof, and durable leakage, using more safe and more comfortable



Strong magnetism

Magnetic strength, which can be installed directly drilling, stable performance.



• Packaging & shipping

SMQT®

danh sách bao bì	
Tên sản phẩm	Emedded cảm xúc từ EB-136
Số lượng	600 chiếc mỗi thùng carton
Kích thước carton	38 * 30 * 30 (cm)
Cân nặng	16kg



• Office show

SMQT®



2011 Brazil Fair



2012 Shenyang Fair



2013 Jinan Fair



2013 Shenzhen Fair





2012 Shenyang Fair



2013 Shenyang Fair



2013 Shenzhen Fair



2015 Shenzhen Fair